

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~strikethrough~~. When strikethrough cannot easily be perceived, or when five or fewer characters are deleted, [[double brackets]] are used to show the deletion. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

Please AMEND claim 41 in accordance with the following:

1. (Cancelled)
2. (Previously presented) A packet processing system comprising:
 - a forwarding device that transmits and receives a packet through a network interface;
 - and
 - a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein
 - the control device includes
 - a symbol section that is associated with address information of the forwarding device; and
 - a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and the forwarding device includes
 - a second transfer control section that sets the packet transfer rule in response to the setting request, wherein
 - the symbol section is a virtual interface corresponding to the network interface,
 - the first transfer control section, when detecting that the application closes a communication port for access to the symbol section, cancels the packet transfer rule in the forwarding device by transmitting to the forwarding device a cancel request that the forwarding device cancels the packet transfer rule, and
 - the second transfer control unit cancels the packet transfer rule in response to the cancel request.

3. (Cancelled)
4. (Previously presented) A packet processing system comprising:
 - a forwarding device that transmits and receives a packet through a network interface;
 - and
 - a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein the control device includes
 - a symbol section that is associated with address information of the forwarding device; and
 - a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and the forwarding device includes
 - a second transfer control section that sets the packet transfer rule in response to the setting request, wherein
 - the symbol section is a virtual interface corresponding to the network interface, and
 - the forwarding device further includes an interface determination section that when receiving from the control device an interface request that the forwarding device provides the network interface to the control device, determines whether the network interface is available.
5. (Previously presented) A packet processing system comprising:
 - a forwarding device that transmits and receives a packet through a network interface;
 - and
 - a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein the control device includes
 - a symbol section that is associated with address information of the forwarding device; and

a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and the forwarding device includes

a second transfer control section that sets the packet transfer rule in response to the setting request, wherein

the symbol section is a virtual interface corresponding to the network interface, and

the packet transfer rule indicates to encapsulate the packet so as to include a tunnel identifier and to transfer the packet between the control device and the forwarding device.

6. (Original) The packet processing system according to claim 5, wherein the tunnel identifier includes

an up-tunnel identifier that is associated with the network interface, a virtual interface corresponding to the network interface, an address of the control device, and a protocol address of the application; and a down tunnel identifier that is associated with a transmission virtual interface for transmitting the packet, an address of the forwarding device, and

a network interface corresponding to the transmission virtual interface.

7. (Previously presented) A packet processing system comprising:

a forwarding device that transmits and receives a packet through a network interface;

and

a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein

the control device includes

a symbol section that is associated with address information of the forwarding device; and

a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and the forwarding device includes

a second transfer control section that sets the packet transfer rule in response to the setting request, wherein
the symbol section is a virtual interface corresponding to the network interface, and
the symbol section is a virtual IP address corresponding to an IP address of the forwarding device.

8. (Previously presented) A packet processing system comprising:
a forwarding device that transmits and receives a packet through a network interface;
and
a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein
the control device includes
a symbol section that is associated with address information of the forwarding device; and
a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and
the forwarding device includes
a second transfer control section that sets the packet transfer rule in response to the setting request, wherein
the symbol section is a virtual interface corresponding to the network interface, and
the packet transfer rule indicates to convert an address of the packet and to transfer the packet between the control device and the forwarding device.

9. (Previously presented) A packet processing system comprising:
a forwarding device that transmits and receives a packet through a network interface;
and
a control device that transfers the packet between the control device and the forwarding device, and responds to the packet using an application, wherein
the control device includes
a symbol section that is associated with address information of the forwarding device; and

a first transfer control section that when detecting that the application accesses the symbol section, sets a packet transfer rule in the forwarding device by transmitting to the forwarding device a setting request that the forwarding device sets the packet transfer rule that is used to transfer the received packet to the control device, and the forwarding device includes

a second transfer control section that sets the packet transfer rule in response to the setting request, wherein

the symbol section is a virtual interface corresponding to the network interface,

the packet transfer rule defines up address conversion and down address conversion,

the up address conversion designates that a destination address of the packet is converted in the forwarding device from a virtual IP address to an address of the control device in the forwarding device, the packet is transferred to the control device, and the destination address of the transmitted packet transmitted is converted from the address of the control device to the virtual IP address in the control device, and

the down address conversion designates that a sender address of the packet is converted from a virtual IP address to an address of the control device in the control device, the packet is transferred to the forwarding device, and the sender address of the transmitted packet is converted from the address of the control device to the virtual IP address.

10. (Cancelled)

11. (Cancelled)

12. (Cancelled)

13. (Previously presented) A method of processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, the control device responding to the packet using an application, the method comprising:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device;

setting the packet transfer rule in response to the setting request in the forwarding device;

transmitting from the control device to the forwarding device a cancel request that the forwarding device cancels the packet transfer rule, when the control device detects that the application closes a communication port for access to the symbol section;

canceling the packet transfer rule in the control device; and

canceling the packet transfer rule in response to the cancel request in the forwarding device and

wherein the symbol section is a virtual interface corresponding to the network interface.

14. (Cancelled)

15. (Previously presented) A method of processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, the control device responding to the packet using an application, the method comprising:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device; and

setting the packet transfer rule in response to the setting request in the forwarding device, wherein

the symbol section is a virtual interface corresponding to the network interface, and

the packet transfer rule defines to encapsulate the packet so as to include a tunnel identifier and to transfer the packet between the control device and the forwarding device.

16. (Previously presented) A method of processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, the control device responding to the packet using an application, the method comprising:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;
setting the packet transfer rule in the control device; and
setting the packet transfer rule in response to the setting request in the forwarding device, wherein
the symbol section is a virtual interface corresponding to the network interface, and
the symbol section is a virtual IP address corresponding to an IP address of the forwarding device.

17. (Previously presented) A method of processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, the control device responding to the packet using an application, the method comprising:

associating a symbol section with address information of the forwarding device;
transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;
setting the packet transfer rule in the control device; and
setting the packet transfer rule in response to the setting request in the forwarding device, wherein
the symbol section is a virtual interface corresponding to the network interface, and
the packet transfer rule defines to convert the address of the packet and to transfer the packet between the control device and the forwarding device.

18. (Cancelled)

19. (Previously presented) A computer-readable recording medium that stores a program for processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, a control device responding to the packet using an application, wherein the program makes a computer execute:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device;

setting the packet transfer rule in response to the setting request in the forwarding device;

transmitting from the control device to the forwarding device a cancel request that the forwarding device cancels the packet transfer rule, when the control device detects that the application closes a communication port for access to the symbol section;

canceling the packet transfer rule in the control device; and

canceling the packet transfer rule in response to the cancel request in the forwarding device and

wherein the symbol section is a virtual interface corresponding to the network interface.

20. (Cancelled)

21. (Previously presented) A computer-readable recording medium that stores a program for processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, a control device responding to the packet using an application, wherein the program makes a computer execute:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device; and

setting the packet transfer rule in response to the setting request in the forwarding device, wherein

the symbol section is a virtual interface corresponding to the network interface, and

the packet transfer rule defines to encapsulate the pack so as to include a tunnel identifier and to transfer the packet between the control device and the forwarding device.

22. (Previously presented) A computer-readable recording medium that stores a program for processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, a control device responding to the packet using an application, wherein the program makes a computer execute:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device; and

setting the packet transfer rule in response to the setting request in the forwarding device, wherein

the symbol section is a virtual interface corresponding to the network interface, and

the symbol section is a virtual IP address corresponding to an IP address of the forwarding device.

23. (Previously presented) A computer-readable recording medium that stores a program for processing a packet between a forwarding device and a control device, the forwarding device transmitting and receiving the packet through a network interface, a control device responding to the packet using an application, wherein the program makes a computer execute:

associating a symbol section with address information of the forwarding device;

transmitting from the control device to the forwarding device a setting request that the forwarding device sets a packet transfer rule that is used to transfer the packet received to the control device, when the control device detects that the application accesses the symbol section;

setting the packet transfer rule in the control device; and

setting the packet transfer rule in response to the setting request in the forwarding device, wherein

the symbol section is a virtual interface corresponding to the network interface, and

the packet transfer rule defines to convert the address of the packet and to transfer the packet between the control device and the forwarding device.

24. (Original) A packet processing system which performs communication with a network node through a network interface of a forwarding device, wherein

the network interface of the forwarding device and an application on a control device are connected to each other by an internal communication path,

the control device includes

a symbol setting unit that sets a symbol section that communicates with the application on the control device and associates it with an interface of the forwarding device;

a first downstream path generation unit that receives from the forwarding device a downstream internal communication path identifier of a downstream internal communication path on which data is transferred in a direction from the symbol section to the interface of the forwarding device, and that generates a first downstream path table where the downstream internal path identifier is associated with the symbol section and an address of the forwarding device;

a first upstream path generation unit that receives a start message that the application starts communicating with the symbol section, that transmits an input-output port identifier of the process and an upstream internal communication path identifier to the forwarding device, and that generates a first upstream path table where the upstream internal path identifier is associated with the symbol section and the input-output port identifier, and

the forwarding device includes

a second downstream path generation unit that generates a second downstream path table where the downstream internal path identifier is associated with the interface of the forwarding device; and

a second upstream path generation unit that generates a second upstream path table where the input-output port identifier of the process, the upstream internal communication path identifier, and the interface are associated with each other.

25. (Original) The packet processing system according to claim 24, wherein

the control device further includes

a first path delete unit that when the application is completed, transmits to the forwarding device a delete request to delete elements of the second upstream path table, and that deletes the elements of the first upstream path table, which corresponds to the completed application, and

the forwarding device further includes

a second path delete unit that deletes the elements of the second upstream path table in response to the delete request.

26. (Original) The packet processing system according to claim 24, wherein the forwarding device further includes an interface manage section that when receiving from the control device an interface request to provide the interface to the control device, determines whether the interface is available.

27. (Original) The packet processing system according to claim 24, wherein the control device further includes

a first path transfer unit that encapsulates a data packet received from the symbol section based on the first downstream path table, that transmits the encapsulated data packet to the forwarding device, when receiving the encapsulated data packet from the upstream path, that decapsulates the packet based on the first upstream path table, and that transfers the data packet to the symbol section, and

the forwarding device further includes

a second path transfer unit that encapsulates a data packet received from the interface based on the second upstream path table, that transmits the encapsulated data packet to the control device, that decapsulates the data packet received from the control device based on the second downstream path table, and that transfers the data packet decapsulated to the interface.

28. (Original) The packet processing system according to claim 24, wherein the symbol section is a virtual interface which corresponds to an interface of the forwarding device.

29. (Original) The packet processing system according to claim 28, wherein the application of the control device is a path control process of a router.

30. (Original) The packet processing system according to claim 24, wherein the control device and the forwarding device are connected to each other through a data link layer, and exchange data there between using a data link layer protocol for exchanging the control message between the control device and the forwarding device.

31. (Original) A method of processing a packet in communication with a network node through a network interface of a forwarding device, wherein the network interface of the forwarding device and an application on a control device are connected to each other by an internal communication path, the method comprising:

- setting a symbol section that communicates with the application on the control device and associates it with an interface of the forwarding device;

- receiving from the forwarding device a downstream internal communication path identifier of a downstream internal communication path on which data is transferred in a direction from the symbol section to the interface of the forwarding device, in the control device;

- generating a first downstream path table where the downstream internal path identifier is associated with the symbol section and an address of the forwarding device;

- receiving a start message that the application starts communicating with the symbol section, in the control device;

- transmitting from the control device to the forwarding device an input-output port identifier of the application and an upstream internal communication path identifier;

- generating a first upstream path table where the upstream internal path identifier is associated with the symbol section and the input-output port identifier;

- generating a second downstream path table where the downstream internal path identifier is associated with the interface of the forwarding device; and

- generating a second upstream path table where the input-output port identifier of the application, the upstream internal communication path identifier, and the interface are associated with each other.

32. (Original) The method according to claim 31, further comprising:

- receiving a complete message that the application is completed, in the control device;

- transmitting from the control device to the forwarding device a delete request to delete elements of the second upstream path table, which corresponds to the completed application;

- deleting the elements of the first upstream path table;

- deleting the elements of the second upstream path table in response to the delete request.

33. (Original) The method according to claim 31, further comprising

determining whether the interface is available when receiving from the control device an interface request to provide the interface to the control device.

34. (Original) The method according to claim 31, further comprising:
- encapsulating a data packet received from the symbol section based on the first downstream path table;
 - transmitting from the control device to the forwarding device the encapsulated data packet;
 - decapsulating the packet based on the first upstream path table when receiving the capsulated data packet from the upstream path;
 - transferring the decapsulated data packet to the symbol section;
 - encapsulating a data packet received from the interface on the forwarding device based on the second upstream path table;
 - transmitting from the forwarding device to the control device the data packet encapsulated;
 - decapsulating the data packet received from the control device based on the second downstream path table; and
 - transferring the decapsulated data packet to the interface.
35. (Original) The method according to claim 31, wherein the symbol section is a virtual interface which corresponds to an interface of the forwarding device.
36. (Original) The method according to claim 35, wherein the application of the control device is a path control process of a router.
37. (Original) The method according to claim 31, wherein the control device and the forwarding device are connected to each other through a data link layer, and exchange data there between using a data link layer protocol for exchanging the control message between the control device and the forwarding device.

38. (Previously presented) A computer-readable recording medium that stores a program for processing a packet in communication with a network node through a network interface of a forwarding device, wherein the network interface of the forwarding device and an application on a control device are connected to each other by an internal communication path, wherein the program makes a computer execute:

- setting a symbol section that communicates with the application on the control device and associates it with an interface of the forwarding device;

- receiving from the forwarding device a downstream internal communication path identifier of a downstream internal communication path on which data is transferred in a direction from the symbol section to the interface of the forwarding device, in the control device;

- generating a first downstream path table where the downstream internal path identifier is associated with the symbol section and an address of the forwarding device;

- receiving a start message that the application starts communicating with the symbol section, in the control device;

- transmitting from the control device to the forwarding device an input-output port identifier of the application and an upstream internal communication path identifier;

- generating a first upstream path table where the upstream internal path identifier is associated with the symbol section and the input-output port identifier;

- generating a second downstream path table where the downstream internal path identifier is associated with the interface of the forwarding device; and

- generating a second upstream path table where the input-output port identifier of the application, the upstream internal communication path identifier, and the interface are associated with each other.

39. (Previously presented) A computer-readable recording medium according to the claim 38, wherein the program further makes the computer execute:

- receiving a complete message that the application is completed, in the control device;

- transmitting from the control device to the forwarding device a delete request to delete elements of the second upstream path table, which corresponds to the completed application;

- deleting the elements of the first upstream path table;

- deleting the elements of the second upstream path table in response to the delete request.

40. (Previously presented) A computer-readable recording medium according to the claim 38, wherein the program further makes the computer execute determining whether the interface is available when receiving from the control device an interface request to provide the interface to the control device.

41. (Currently amended) A computer-readable recording medium according to the claim 38, wherein the program further makes the computer execute:

encapsulating a data packet received from the symbol section based on the first downstream path table;

transmitting from the control device to the forwarding device the encapsulated data packet;

~~decapsulating~~decapsulating the packet based on the first upstream path table when receiving the capsulated data packet from the upstream path;

transferring the decapsulated data packet to the symbol section;

encapsulating a data packet received from the interface on the forwarding device based on the second upstream path table;

transmitting from the forwarding device to the control device the encapsulated data packet;

decapsulating the data packet received from the control device based on the second downstream path table; and

transferring the decapsulated data packer to the interface.

42. (Previously presented) A computer-readable recording medium according to claim 38, wherein the symbol section is a virtual interface which corresponds to an interface of the forwarding device.

43. (Previously presented) A computer-readable recording medium according to claim 42, wherein the application of the control device is a path control process of a router.

44. (Previously presented) A computer-readable recording medium according to claim 38, wherein the control device and the forwarding device are connected to each other through a data link layer, and exchange data there between using a data link layer protocol for exchanging the control message between the control device and the forwarding device.